


R150





R220

| | | LED Power | Lumens (at 3000K) | Beam | Weight |
|---|---|---|---|---|---|
| 1 | **R150 Track** | 15W (400mA) | 1017lm | 110° | 800g |
| 2 | **R220 Track** | 20W (500mA) | 1536lm | 110° | 1.1kg |

| Key Information | |
|---|---|
| Mounting | Track |
| Finish | Textured Black<br>Textured White |
| LED CCT | 3000K<br>4000K |
| Warranty | 5 Years |

| Design | |
|---|---|
| Product Family | Akira |
| Adjustability | 350° Rotation, 80° Tilt |
| Material | Powder Coated Aluminium, Polycarbonate Diffuser |
| IP Rating | IP20 |
| Class Rating | Class II |

| Performance | |
|---|---|
| Lumen Efficacy | Up to 77lm/W |
| CRI (Ra/R9) | 90+ (R9: >50) |
| UGR (70/50/20) | <19 |
| Lifetime (Ta 25°C) | >50,000h L70B10 |
| Operating Ambient Temperature | -10°- 35°C |
| SDCM | ≤3 |
| COI Compliance Model Requirements | 4000K |

| Track & Driver Compatibility | |
|---|---|
| Phase Cut | MX3 In-Track |
| DALI | MX5 In-Track |
| Bluetooth | MX5 In-Track |

