

Node Recessed




1



Node 1



2



Node 5




3



Node 10



4



Node 15

		LED Power	Lumens (at 3000K)	Beam	Weight	Driver Options
1	**Node 1**	2W (700mA)	176lm	46°	90g	Non-Dim, DALI, Bluetooth
2	**Node 5**	10W (700mA)	859lm	46°	345g	Phase Cut, DALI, Bluetooth
3	**Node 10**	20W (700mA)	1822lm	46°	690g	Phase Cut, DALI, Bluetooth
4	**Node 15**	30W (700mA)	2348lm	46°	1.0kg	Phase Cut, DALI, Bluetooth

Key Information	
Mounting	Ceiling Recessed
Finish	■ Textured Black □ Textured White/Black
LED CCT	2700K 3000K 4000K
Warranty	5 Years

Design	
Product Family	Node
Material	Powder Coated Aluminium
IP Rating	IP20
Class Rating	Class II
Insulation Rating	IC

Performance	
Lumen Efficacy	Up to 77lm/W
CRI (Ra/R9)	90+ (R9: >50)
UGR (70/50/20)	<10
Lifetime (Ta 25°C)	>66,000h L90B10
Operating Ambient Temperature	-10°- 35°C
SDCM	≤3
COI Compliance Model Requirements	4000K

Driver	
Non-Dim	Remote
Phase Cut	Remote
DALI	Remote
Bluetooth	Remote

Driver Notes

Node 1 must be wired in series in groups of 3-4 for dimmable solutions.

